

Příloha č. 1 zadávací dokumentace - Seznam požadovaných komponent

Označení	Popis komponenty	Počet
VS-S2T-10G=	Cat 6500 Sup 2T with 2 x 10GbE and 3 x 1GbE with MSFC5 PFC4	2
S2TAIK9-12250SY	Cisco CAT6000-VS-S2T IOS ADVANCED IP SERVICES FULL ENCRYPT	2
MEM-C6K-INTFL1GB	Internal 1G Compact Flash	2
VS-F6K-PFC4	Cat 6k 80G Sys Daughter Board Sup2T PFC4	2
VS-SUP2T-10G	Catalyst 6500 Supervisor Engine 2T Baseboard	2
MEM-SUP2T-2GB	Catalyst 6500 2GB memory for Sup2T and Sup2TXL	2
X2-10GB-SR	10GBASE-SR X2 Module	2
X2-10GB-LRM	10GBASE-LRM X2 Module	2
WS-X6816-10G-2T=	16 Port 10G with DFC4	1
WS-F6K-DFC4-E	Catalyst 6500 Dist Fwd Card DFC4	1
WS-X6816-10GE	6816 10G baseboard	1
WS-X6824-SFP-2T=	Catalyst 6500 24-port GigE Mod: fabric-enabled with DFC4	2
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver	2
GLC-SX-MM	GE SFP, LC connector SX transceiver	2
WS-F6K-DFC4-A	Catalyst 6500 Dist Fwd Card DFC4	2
WS-X6824-SFP	24 port 1G SFP based Baseboard	2
X2-10GB-SR-OEM	X2 transceiver 10GBASE-SR, MM, OM3-300/OM2-85/OM1-33m, 850nm, SC Duplex, Cisco kompatibilní, DMI diagnostika	2
X2-10GB-LR-OEM	X2 transceiver 10GBASE-LR, SM, 10km, 1310nm, SC Duplex, Cisco kompatibilní, DMI diagnostika	2
GLC-LH-SM-OEM	SFP transceiver 1,25Gbps, 1000BASE-LX, SM, 20km, 1310nm FP), LC duplex, 0 až 70°C, 3,3V, Cisco kompatibilní	2
GLC-SX-MM-OEM	SFP transceiver 1,25Gbps, 1000BASE-SX, MM, 300/550m, 850nm (VCSEL), LC duplex, 0 až 70°C, 3,3V, Cisco kompatibilní	2